



PLASTIC STRAPPING SYSTEMS
MODEL SERIES: CP 500



CP 500

The pneumatic hand tool CP 500 can hardly be beaten and is ideal for companies that have to pack heavy goods and strap them on strapping stations ready for despatch.

The unique construction allows a high tension force of up to 5,000 N* with continuously high retaining strength thus keeping the load secure until it reaches its destination.

Technical data	Weight:	Approx. 5,6 kg
	Dimensions LxWxH:	300 x 155 x 200 mm
	Tension force:	Up to 5,000 N* (* depending on the strap quality and package)
	Seal:	Friction weld
	Tensioning speed:	7 m/min.
Strap	Strap type:	Polyester (PET) and Polypropylene (PP)
	Strap dimensions:	Width: 12 / 16 / 19 / 25 mm Thickness: 0,7 – 1,4 mm
Technical requirements	Air pressure:	6 bar (max. 7 bar)
	Pipe inner dia.:	3/4"
	Hose dia.:	3/8"
Accessories	Universal hanger for stationary strapping	
Options	Steel plate as protection of the base area against wear	
Characteristics	<ul style="list-style-type: none">• Pneumatic strapping hand tool• Adjustable to various strap widths• Tensionless seal possible	
Advantages	<ol style="list-style-type: none">1. Easy handling2. Simple insertion – strap on strap3. High tension for industrial requirements4. Very strong seal5. Light, compact, ergonomic6. Maintenance-friendly	

WWW.CYKLOP.COM

DIRECT LINE: +49 (0) 2236 602 0

CYKLOP GmbH
Industriestraße 133
50996 Cologne
Germany
info@cyklop.de

CYKLOP
INTERNATIONAL

THE
STRAPPING
COMPANY

100 YEARS
1912/2012