

Low-cost and reliable semi-automatic strapping machine is now ready from band-A-matic. The BONITO-3 offers what you want!

MICROCOMPUTER CONTROL

Microcomputer controlled system enables reliable, stable performance in tensioning.

HOUSEHOLD VOLTAGE

The Bonito is powered from a standard single-phase electrical socket, so it can be used without difficulty in any office and shop.

WIDE VARIETY OF STRAP

Adjustable strap ranging from 5mm -15.5mm of width can be utilized without changing parts. Also, various kinds of straps, such as polypropylene, elastic, formed, etc can be utilized on Bonito.

SIMPLE DESIGN, BUT HIGH PERFORMANCE

Simplifying its design, minimizing its functions, this Bonito must be one of ideal semi-automatic strapping machines in the market. Its cost performance can be realized only by those who use the machine and would recognize that the low cost machine is not always low quality.



Standard Specifications

Name	Semi-Automatic Strapping Machine
Model	Bonito-3
Dimensions	L760mm×D541.50mm×H740mm
Weight	Approx. 68Kg
Speed	2~3 seconds/cycle
Sealing method	Heat seal
Control	Microcomputer control
Tension	Max. 490N (50Kgf)
Strap Width	Width 5mm ~ 15.5mm
Strap core I.D	200mmφ (Option: 230mm, 280mm)
Body color	Light gray
Power source	1P, 110V/120V/230V, 50/60Hz
Power consumption	300W

Dimensions



※Specifications and appearance are subject to change without notice.

DISTRIBUTED BY

EXPORTER:

SHIBAMOTO & CO.,LTD.

1-12, MINATO 1-CHOME, CHUO-KU, TOKYO 104-0043, JAPAN
TEL : +81-3-3553-8307 FAX : +81-3-3552-4877
E-mail : bandamatic@shibamoto.jp

MANUFACTURER:

NAIGAI, LIMITED

1-12, MINATO 1-CHOME, CHUO-KU, TOKYO 104-0043, JAPAN
URL : <http://www.bandamatic.com>